
Wall Mounted Cell Phone Jammer - 30m Shielding Radius

Main Features:

- Devices Blocked: All Cell Phones
- Signal Blocked: IDEN, TDMA, CDMA, GSM,3G and UMTS;AMPS, NMT, N-AMPS, TACS;
- Effective Coverage: 30 Metres

Images:



Technic Specifications:

- Isolating Signal Bandwidth:
 - CDMA800: 850-894MHz; 33dBm; 6dBm/30KHz (min)
 - GSM900: 920-960MHz; 33dBm; 5dBm/30KHz (min)
 - DCS1800: 1805-1880MHz; 33dBm; 2dBm/30KHz (min)
 - PHS 1900: 1895-1920MHz; 33dBm; 2dBm/30KHz (min)
 - GSM1900: 1930-1990MHz; 33dBm; 2dBm/30KHz (min)
 - 3G: 2110-2170MHz; 33dBm; 2dBm/30KHz (min)
- Blocking Coverage: 30 Meters
- Total output power: 8W (CDMA800:2W, GSM900:2W, 1805-1990: 2 W, 2100-2200: 2W)
- Signal Source PLL synthesized
- Antennas External Omni directional
- Every band frequency can select output power
- All the TX frequency covered down link only
- AC adapter (AC220V-DC5V)
- Typical Battery Life: 3 Hours
- Shielding Radius: (10-30) meters,-75dBm Rules of installation: UL (E190582) CSA (LR 112971 Level 3)
- Weight: 2KG

Package Included:

- 1pc Wall Mounted Cell Phone Jammer - 30m Shielding Radius
- 1pc Power Adapter (100-240V)
- 1pc Manual

Important Notice:

The item is for Legal Use only!

[product_url:] [Wall Mounted Cell Phone Jammer - IDEN, TDMA, CDMA, GSM,3G and UMTS;AMPS, NMT, N-AMPS, TACS](#)

[pdf_url:] <http://www.smdsinai.org/WallMountedCellPhoneJammerIDENTDMACDMAGSM3GandUMTSAMPSNMTNAMPS>
